

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 207 671 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
22.05.2002 Bulletin 2002/21

(51) Int Cl.7: **H04M 1/02**

(21) Application number: **01127322.4**

(22) Date of filing: **19.11.2001**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(71) Applicant: **NEC CORPORATION**  
**Tokyo (JP)**

(72) Inventor: **Ozaki, Kazuya**  
**Minato-ku, Tokyo (JP)**

(30) Priority: **20.11.2000 JP 2000353030**


(74) Representative: **VOSSIUS & PARTNER**  
**Siebertstrasse 4**  
**81675 München (DE)**

(54) **Opening/closing structure for a portable information terminal**

(57) In an opening/closing type portable information terminal equipped with a display portion housing (1) having a display portion (3) and an operating portion housing (2) having an operating portion (5), under the state that the face of the operating portion (5) of the operating portion housing (2) and the face of the display

portion (3) of the display portion housing (1) face in the same side, the end portion of the display portion housing (1) and the end portion of the operating portion housing (2) are linked to each other by a link member (7) so that the display portion housing (1) is rotatable to the operating portion housing (2) around the rotational axis (CX) of the link member (7).

**FIG.1B**



## Description

[0001] The present invention relates to an opening/closing type portable information terminal having such a structure that a display portion housing having a display portion and an operating portion housing having an operating portion are separately provided so that the display portion housing and the operating portion housing are opened/closed.

[0002] A using style for cellular phones has been recently varied from a using style as a telephone to a using style as a portable information terminal or personal digital assistants (PDA) for the Internet, electronic mails, schedule management, etc. The cellular phones are often designed to have such a structure that a display portion housing having a liquid crystal display portion for performing various kinds of displays and an operating portion housing having operating keys are freely opened/closed around a hinge portion so that they are foldable with the liquid crystal display portion disposed inside, whereby a liquid crystal display portion having a large screen can be mounted on the display portion housing and the cellular phones can be used as portable information terminals or personal digital assistants for the Internet, electronic mails, etc. JP(A)-11-284700 and JP(A)-11-330716 disclose such a foldable type of cellular phones.

[0003] In an opening/closing type cellular phone with a liquid crystal display portion having a large screen as described above, a user cannot see the liquid crystal display portion when the two housings are folded. Therefore, when an electronic mail is received or the like, the user must see the electronic mail under the state that the liquid crystal display portion housing and the operating portion housing are kept open. Accordingly, it is inconvenient for a user to open/close a cellular phone every time an electronic mail is received.

[0004] The present invention has been implemented in view of the foregoing problem of the prior art, and has an object to provide an opening/closing type portable information terminal or PDA which enables a user to see a display portion under the state that a display portion housing and an operating portion housing are closed, thereby enhancing its convenience for users.

[0005] In order to attain the above object, according to the present invention, an opening/closing type portable information terminal equipped with a display portion housing having a display portion and an operating portion housing having an operating portion is characterized in that an end portion of the display portion housing is linked or connected to an end portion of the operating portion housing by a rotating mechanism under the state that the face of the display portion of the display portion housing is maintained to orient in the same side as the face of the operating portion of the operating portion housing so that the display portion housing and the operating portion housing are rotatable to each other around the rotational axis of the rotating mechanism.

The rotational axis extends in a direction intersecting the face of the operating portion and the face of the display portion.

[0006] According to the present invention, there is also provided an opening/closing type portable information terminal, comprising:

a display portion housing having a display portion;  
an operating portion housing having an operating portion; and  
a rotating mechanism for rotating the display portion housing relative to the operating portion housing between a closed state in which the display portion housing is disposed so as to cover the operating portion and an open state in which the display portion housing is disposed so as not to cover the operating portion,

wherein an end portion of the display portion housing and an end portion of the operating portion housing are rotatably connected to each other by the rotating mechanism in such a manner that a face of the display portion is oriented in the same side as a face of the operating portion at both the closed state and open state.

[0007] According to the present invention, by linking the end portion of the display portion housing and the end portion of the operating portion housing to each other through the rotating mechanism under the state that the face of the display portion of the display portion housing and the face of the operating portion of the operating portion housing are maintained to face in the same side at both the closed and open states, the user can see the display portion of the display portion housing even when the display portion housing and the operating portion housing are closed. Accordingly, for example when an electronic mail is received or they are used as an electronic pocketbook, the information terminal can be used without opening the display portion housing and the operating portion housing (i.e., under the state that they are closed), and a convenient portable information terminal can be implemented.

[0008] Further, the display portion of the display portion housing and the operating portion of the operating portion housing face in the same side even when the display portion housing and the operating portion housing are opened, so that the user can operate the operating portion while seeing the display portion like the conventional cellular phone. Therefore, the facility is not lost. Further, when the present invention is applied to an opening/closing type cellular phone, under the state that the display portion housing and the operating portion housing are opened, the ear and mouth of the user are near to the speaker and the microphone respectively because a predetermined angle is kept between the display portion and the operating portion, so that the device of the present invention is convenient as a cellular phone.

Figs. 1A and 1B are diagrams showing the construction of an embodiment of an opening/closing type portable information terminal according to the present invention;

Figs. 2A, 2B, 2C and 2D are enlarged views showing a link portion of the portable information terminal according to the embodiment shown in Figs. 1A and 1B and its variation;

Figs. 3A, 3B and 3C are diagrams showing the closed state of the portable information terminal of the embodiment shown in Figs. 1A and 1B;

Fig. 4 is a diagram showing the opening operation of the portable information terminal of the embodiment of Figs. 1A and 1B;

Fig. 5 is a diagram showing the opening operation of the portable information terminal of the embodiment of Figs. 1A and 1B; and

Figs. 6A, 6B and 6C are diagrams showing the open state of the portable information terminal according to the embodiment of Figs. 1A and 1B.

**[0009]** Preferred embodiments according to the present invention will be described hereunder with reference to the accompanying drawings.

**[0010]** Figs. 1A and 1B are front and side views showing the construction of an embodiment of an opening/closing type portable information terminal or personal digital assistants (PDA) according to the present invention. The following embodiment will be described on the assumption that a cellular phone is representatively used as an opening/closing type portable information terminal. In the following embodiment, it is assumed that the cellular phone has not only functions as a telephone, but also has functions of a portable information terminal such as an electronic mail, an electronic pocketbook, etc., for example.

**[0011]** In Figs. 1A and 1B, reference numeral 1 represents a display portion housing formed of synthetic resin or the like, and reference numeral 2 represents an operating portion housing formed of synthetic resin or the like. The display portion housing 1 is equipped with a liquid crystal display portion 3 having a large screen and a speaker 4 at the same side, and the operating portion housing 2 is equipped with an operating portion 5 comprising plural keys, and a microphone 6 at the same side. Further, the display portion housing 1 is also equipped with operating keys 8 at the same side as the display portion 3. An angle  $\theta$  is kept between faces of the liquid crystal display portion 3 and the operating portion 5 as shown in Fig. 1B. The angle  $\theta$  is within the range of 110 to 180 degrees, preferably 130 to 170 degrees, for example.

**[0012]** In the display portion housing 1 and the operating portion housing 2 are provided various circuits and various mechanisms that implement the functions as a cellular phone and the functions as a portable information terminal for electronic mails, etc. The descriptions of these circuits and mechanisms are omitted from the

following description. Further, an antenna for receiving/transmitting electric waves is provided to the display portion housing 1, however, it is omitted from the drawings.

**[0013]** Figs. 2A and 2B are enlarged cross-sectional views of a link portion between the display portion housing 1 and the operating portion housing 2. The link structure or connection structure of the display portion housing 1 and the operating portion housing 2 will be described with reference to Figs. 2A and 2B, etc.

**[0014]** One end portion of the display portion housing 1 and one end portion of the operating portion housing 2 are linked or connected to each other by a link member 7 so that the display portion housing 1 is rotatable relative to the operating portion housing 2 around the link member 7, especially around the rotational axis CX.

**[0015]** The link member 7 is provided as a rotating mechanism, and it is formed of synthetic resin or the like. The link member 7 is designed in the form of a cylinder having a cavity portion 7a therein passing therethrough along the rotational axis CX, and flange portions or guide portions 7b are formed at the upper and lower portions of the link member 7 so as to project radially outwardly. As shown in Fig. 2A, the link member 7 is embedded in each of the display portion housing 1 and the operating portion housing 2 half-and-half, that is, the upper and lower guide portions 7b are respectively embedded in the cavity portions of the display portion housing 1 and the operating portion housing 2 with being pressed against the inner wall surfaces of the housings. Such a structure is shown in Fig. 2C in detail.

**[0016]** The upper and lower guide portions 7b of the link member 7 are provided so that the display portion housing 1 and the operating portion housing 2 are prevented from being detached from the link member 7 to ensure the link of the housings and also the display portion housing 1 and the operating portion housing 2 can be smoothly rotated around the guide portion 7b of the link member 7 because the outer periphery of each guide portion 7b is circular. Since the link member 7 is embedded in the display portion housing 1 and the operating portion housing 2 while pressed against the housings 1 and 2, the display portion housing 1 and the operating portion housing 2 can be rotated to each other around the link member 7, especially around the rotational axis CX.

**[0017]** One of the guide portion 7b of the link member 7 may be fixed to any one of the display portion housing 1 and the operating portion housing 2. Further, as shown in Fig. 2C, a spring 10 may be provided around the outer peripheral portion of the link member 7 between the display portion housing 1 and the operating portion housing 2. That is, by pressing the display portion housing 1 and the operating portion housing 2 outwardly to each other under the spring force, the display portion housing 1 and the operating portion housing 2 can be prevented from coming into contact with each other or occurrence of backlash can be prevented when they are rotated

around the link member 7, so that they can be smoothly rotated.

**[0018]** An inclined surface 2a which is inclined at an angle of  $(180^\circ - \theta)/2$  with respect to the surface of the operating portion 5 is formed in the operating portion housing 2 at the link portion as shown in Fig. 2A, and the link member 7 is disposed as to be inclined with respect to the face of the operating portion 5 and bottom surface of the operating portion housing 2 in accordance with the inclined surface 2a of the operating portion housing 2. The rotational axis CX is perpendicular to the inclined surface 2a. This structure keeps the angle  $\theta$  between the operating portion housing 2 and the display portion housing 1, especially between the face of the display portion 3 and each of the face of the operating portion 5 and the back surface of the display portion housing 1, under the state that the display portion housing 1 and the operating portion housing 2 are opened as shown in Fig. 1B.

**[0019]** That is, as described above, the display portion housing 1 is provided with the speaker 4, and the operating portion housing 2 is provided with the microphone 6. Therefore, by keeping the angle  $\theta$  appropriately between the display portion housing 1 and the operating portion housing 2, the ear of a user is near to the speaker 4 and the mouth of the user is near to the microphone 6 when the portable information terminal is used as a cellular phone. Accordingly, the portable information terminal of this embodiment achieves characteristics having the same level as a conventional folding type cellular phone in the sound quality of received call and transmitting call. As shown in Fig. 2C, the cavity portion 7a of the link member 7 is provided to pass a communication cable 11 therethrough, and the communication cable 11 is passed through the cavity portion 7a to electrically connect the circuits located in the display portion housing 1 and the circuits located in the operating portion housing 2.

**[0020]** Figs. 3A to 3C are front, plan and side views showing the state that the cellular phone of this embodiment is closed. Under the state that the display portion housing 1 and the operating portion housing 2 of the cellular phone are closed and the display portion housing 1 covers the operating portion 5, the liquid crystal display portion 3 faces outwardly, which is opposite to the conventional folding type cellular phone. Therefore, for example when an electronic mail is received, a user can see the mail displayed on the liquid crystal display portion 3 while the display portion housing 1 and the operating portion housing 2 are closed. Likewise, when the portable information terminal of this embodiment is used as an electronic pocketbook, it can be used while the display portion housing 1 and the operating portion housing 2 are closed.

**[0021]** Furthermore, since the display portion housing 1 is provided with the operating keys 8, the portable information terminal of this embodiment can be used while the display portion housing 1 and the operating portion

housing 2 are kept closed. In this case, however, the area of the display portion housing 1 for mounting the operating keys 8 is limited, and thus only a small number of operating keys 8 can be mounted there. Therefore, there are provided only operating keys necessary to carry out simple operations such as seeing an electronic mail on the liquid crystal display portion 3 when the electronic mail is received, seeing a schedule of an electronic pocketbook, etc. under the state that the display portion housing 1 and the operating portion housing 2 are closed.

**[0022]** Figs. 4 and 5 show the opening operation of the operating portion housing 2 and the display portion housing 1. The display portion housing 1 and the operating portion housing 2 are linked to each other by the link member 7. Therefore, when the display portion housing 1 is opened with respect to the operating portion housing 2 as shown in Fig. 4, the liquid crystal display portion housing 1 is rotated around the link member 7. When the display portion housing 1 is further opened, the display portion housing 1 is further rotated around the link member 7 as shown in Fig. 5 to keep the display portion housing 1 to be opened with respect to the operating portion housing 2 by 180 degrees.

**[0023]** Figs. 6A to 6C are front, plan and side views showing the state that the display portion housing 1 and the operating portion housing 2 are opened. Under the state that the display portion housing 1 and the operating portion housing 2 are opened and the display portion housing 1 does not cover the operating portion 5, the ear and mouth of a user are near to the speaker 4 and the microphone 6 respectively because the angle  $\theta$  is kept appropriately between the display portion 3 and the operating portion 5 as mentioned in the above, and this is very convenient for the user.

**[0024]** Furthermore, under the state that the display portion housing 1 and the operating portion housing 2 are opened, the liquid crystal display portion 3 of the display portion housing 1 and the operating portion 5 of the operating portion housing 2 face in the same side like the conventional folding type cellular phone, so that the user can manipulate the keys of the operating portion 5 and keys 8 while seeing the liquid crystal display portion 3, and this is convenient for the user. Still further, under this state, the cellular phone of this embodiment can be also used as a portable information terminal for electronic mails, an electronic pocketbook, etc. by operating the keys of the operating portion 5.

**[0025]** In case that the lower guide portion 7b of the link member 7 is fixed to the operating portion housing 2, the rotation of the display portion housing 1 around the link member 7 is preferably restricted within the range of 180 degrees, i.e. from the closed state of Figs. 3A to 3C to the open state of Figs. 6A to 6C. Fig. 2D shows an embodiment of means for performing such restriction of the rotation, in which a groove 7b' is formed on the outer periphery of the upper guide portion 7b so as to extend slightly greater than 180 degrees around

the rotational axis CX, and a projection 1' is formed on the inner surface of the display portion housing 1 so as to be in engagement with the groove 7b'.

[0026] In the foregoing description, the present invention is applied to an opening/closing type cellular phone. However, the present invention is not limited to the cellular phone, and it may be applied to an opening/closing type portable information terminal or personal digital assistants (PDA) such as an electronic pocketbook, a compact computer or the like. Further, in the above-described embodiment, the cylindrical link member having a cavity therein is used as the rotating mechanism. However, the present invention is not limited to this rotating mechanism, and various rotating mechanism performing substantially the same rotation may be used.

### Claims

1. An opening/closing type portable information terminal equipped with a display portion housing having a display portion and an operating portion housing having an operating portion, **characterized in that** an end portion of said display portion housing is linked to an end portion of said operating portion housing by a rotating mechanism under the state that the face of the display portion of said display portion housing is maintained to orient in the same side as the face of the operating portion of said operating portion housing so that said display portion housing is rotatable relative to said operating portion housing around the rotational axis of said rotating mechanism.
2. The opening/closing type portable information terminal as claimed in claim 1, wherein said rotating mechanism comprises a link member that is designed in the form of a cylinder having a cavity portion therein and provided with guide portions projecting outwardly at the upper and lower portions thereof, and said upper and lower guide portions are embedded in said display portion housing and said operating portion housing while pressed against said display portion housing and said operating portion housing.
3. The opening/closing type portable information terminal as claimed in claim 2, wherein a communication cable for electrically connecting circuits located in said display portion housing to circuits located in said operating portion housing passes through said cavity portion of said rotating mechanism.
4. The opening/closing type portable information terminal as claimed in claim 1, 2 or 3, wherein said rotating mechanism is disposed while inclined with respect to the face of said operating portion, and a predetermined angle is kept between the face of

said display portion and the face of said operating portion under the state that said display portion housing and said operating portion housing are opened.

5. The opening/closing type portable information terminal as claimed in claim 2, 3 or 4, wherein one of said upper and lower guide portions of said link member are fixed to any one of said display portion housing and said operating portion housing.
6. The opening/closing type portable information terminal as claimed in any of claims 1 to 5, wherein a spring is provided around said rotating mechanism to press said display portion housing and said operating portion housing outwardly.
7. The opening/closing type portable information terminal as claimed in any of claims 1 to 6, wherein said display portion housing is provided with operating keys which are operable under the state that said display portion housing and said operating portion housing are closed.
8. An opening/closing type portable information terminal, comprising:
  - a display portion housing having a display portion;
  - an operating portion housing having an operating portion; and
  - a mechanism for rotating said display portion housing relative to said operating portion housing between a closed state in which said display portion housing is disposed so as to cover said operating portion and an open state in which said display portion housing is disposed so as not to cover said operating portion,

wherein an end portion of said display portion housing and an end portion of said operating portion housing are rotatably connected to each other by said mechanism for rotating in such a manner that a face of said display portion is oriented in the same side as a face of said operating portion at both said closed state and said open state.

FIG. 1A




FIG. 1B




FIG.2A




FIG.2B




FIG.2C




FIG.2D




FIG.3A




FIG.3B




FIG.3C






FIG.4




FIG.5




FIG. 6B




FIG. 6C






FIG. 6A





Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 207 671 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
07.05.2003 Bulletin 2003/19

(51) Int Cl.7: **H04M 1/02, G06F 1/16**

(43) Date of publication A2:  
22.05.2002 Bulletin 2002/21

(21) Application number: **01127322.4**

(22) Date of filing: **19.11.2001**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(71) Applicant: **NEC CORPORATION**  
**Tokyo (JP)**

(72) Inventor: **Ozaki, Kazuya**  
**Minato-ku, Tokyo (JP)**

(30) Priority: **20.11.2000 JP 2000353030**


(74) Representative: **VOSSIUS & PARTNER**  
**Siebertstrasse 4**  
**81675 München (DE)**

(54) **Opening/closing structure for a portable information terminal**

(57) In an opening/closing type portable information terminal equipped with a display portion housing (1) having a display portion (3) and an operating portion housing (2) having an operating portion (5), under the state that the face of the operating portion (5) of the operating portion housing (2) and the face of the display

portion (3) of the display portion housing (1) face in the same side, the end portion of the display portion housing (1) and the end portion of the operating portion housing (2) are linked to each other by a link member (7) so that the display portion housing (1) is rotatable to the operating portion housing (2) around the rotational axis (CX) of the link member (7).

**FIG. 1 B**



**EP 1 207 671 A3**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 01 12 7322

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 485 517 A (GRAY ROBERT R) 16 January 1996 (1996-01-16)	1,4,8	H04M1/02 G06F1/16
A	* column 5, line 50 - column 10, line 55; figures 1-13 *	2,5,6	
X	US 5 973 915 A (EVANS D SCOTT) 26 October 1999 (1999-10-26)	1,8	
A	* column 1, line 22 - line 24 * * column 3, line 18 - line 26; figures 1,2 * * column 4, line 5 - line 42; figures 6-8 *	2,5,6	
X	US 5 638 257 A (KUMAR RAJENDRA ET AL) 10 June 1997 (1997-06-10)	1,8	
A	* column 2, line 15 - column 3, line 38; figures 1-3 *	2,5	
X	US 6 009 336 A (WILLIAMS DANIEL L ET AL) 28 December 1999 (1999-12-28)	1,7,8	TECHNICAL FIELDS SEARCHED (Int.Cl.7)  H04M G06F
A	* column 2, line 40 - line 45; figures 10-13 * * column 5, line 45 - line 46; figure 8 * * column 7, line 23 - column 9, line 5; figures 5,6 *	3,6	
A	US 5 751 544 A (SONG KWANG-HO) 12 May 1998 (1998-05-12)	2,3	
	* column 3, line 55 - column 5, line 19; figures 1-4 *		
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>17 March 2003</b>	Examiner <b>Ayala Perriello, M</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503.03.02 (P/M/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 12 7322

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-03-2003

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5485517	A	16-01-1996	NONE		
US 5973915	A	26-10-1999	NONE		
US 5638257	A	10-06-1997	US	5548477 A	20-08-1996
			AU	4906896 A	14-08-1996
			EP	0827605 A1	11-03-1998
			WO	9623251 A1	01-08-1996
US 6009336	A	28-12-1999	CN	1170329 A ,B	14-01-1998
			DE	19726602 A1	29-01-1998
			GB	2351201 A ,B	20-12-2000
			GB	2315186 A ,B	21-01-1998
			JP	10098561 A	14-04-1998
US 5751544	A	12-05-1998	KR	156801 B1	16-11-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82